

2003 Catalog Correction Bulletin

Following are known corrections to catalog number 305. Please keep this page as a permanent supplement to your catalog.

Notations:

<u>Page #</u>	<u>IPC Part #</u>	<u>Note:</u>
C3	All shown	Column identified as "Plain Copper", should be "Plain Aluminum".
D1	A60U	Part should be correctly identified as A60UB
D3	A240D	Part number should be deleted. Use part number A240B
D3	240U	Picture shown is incorrect. See new picture below.
D5	60SS & A60SS	Accepts standing seams for up to 3/4" wide.
D5	60 & 60B	Check pictures. Our first printing had these pictures reversed. Descriptions are correct.
D8	67B	Part has 1/2" inside threads.
	E17	597D & A597D Parts now obsolete. Use 597C or A597C
E18	597A, A597A 597B & A597B	Parts are replaced by 170CP and 170AP
F3	121SS & A121SS	Accepts standing seams for up to 3/4" wide.
J3	535X & 538X Series	Pictures are reversed in the catalog.

Corrections/Additions:

#240U - Bronze Concealed Base Assembly. This base is for use with air terminals that have 5/8" inside threads. See below. Assembly includes 3/8" x 15" stem of which top 6" is threaded, neoprene washer, nut, 63Y adaptor and cable clamp. Wt. .90 lb. ea.



#240U



#A60UADP - Universal Adaptor. Made of aluminum, with 1/2" OD and 5/8" ID threads to use with 5/8" air terminal. Wt. .05 lb. ea. (no picture)

#181C - Copper Strap-Railing Cable Clamp. Fits railings or pipes up to 1 3/4" diameter. Additional lengths available upon request. Wt. .12 lb. ea.

#A181C - Aluminum Strap-Railing Cable Clamp. Wt. .06 lb. ea.



#181C



#181C in application



Independent Protection Co., Inc.

P.O. Box 537

Goshen, IN. 46527-0537

574.533.4116

Fax: 574.534.3719

info@ipclp.com www.ipclp.com

Corrections/Additions Cont.:



UL
LISTED
45H2

#597C - Bronze Thru-Roof for 1" up to 2" PVC Conduit. Consists of 170CP bronze protector cap with 60U bronze cable connector, 1/2" x 8" length threaded stem, 179 base plate and bottom cable connector. Wt. 1.82 lb. ea.

#A597C - Aluminum Thru-Roof 1" up to 2" PVC Conduit Connector. Wt. .92 lb. ea.

#597BM - Bimetallic Thru-Roof for 1" up to 2" PVC Conduit Connector, consists of 170AP aluminum cap with A60U aluminum cable connector, 1/2" x 8" length threaded stainless steel stem, with 179 bronze base plate and bronze bottom cable connector. Wt. 1.10 lb. ea.

Please Note: The PVC shown in the assembly photo is for illustrative purposes only. The PVC is provided by the installing dealer contractor or by others on the job site. Longer threaded stems are available upon request.



#170CP - Copper PVC Cap for use with all 597 assemblies. Specify thread size when ordering. Cap may be used for 1" to 2" PVC. 170CP Wt. .28 lb. ea.

#170AP - Aluminum PVC Cap. Same as above except in aluminum. Wt. .10 lb. ea.



#170CP - Copper Flat Head Point Tip Protector. Flat head protector is offered as a safety item to be placed on top of threaded air terminals. When ordering air terminals, which are sold separately, specify 3/8", 1/2" or 5/8" threads. Wt. .28 lb. ea.

#170AP - Aluminum Flat Head Point Tip Protector. Same as above except in aluminum. Wt. .10 lb. ea.

If you find additional errors or incorrect information in this catalog, please call our office for correction.

Thank you!